

AMENDMENTS TO THE CLAIMS:

The following listing of claims will replace all prior versions of claims in the present application. Claims 21, 23, 28, and 30-34 are currently amended. Please cancel claims 22, 27, and 36-40. Claims 1-20 were cancelled by a prior amendment.

Listing of Claims:

Claims 1-20 have been cancelled.

21. (Currently amended) A method of manufacturing at least one device defining a volume for retaining a fluid or a sensitive material that is capable of changing its physical properties, particularly its optical properties, via the application of a voltage, or its electrical properties via stress or radiation, said device including at least a first front substrate and at least a second back substrate maintained at a constant distance from each other, these two substrates being joined by a sealing joint which defines the volume for retaining the sensitive medium or fluid,

wherein said method includes the following steps in the sequence set forth:

- structuring on one of the substrates, at least one filling channel defined by an inner wall and an outer wall, which extend at a distance from each other, the inner wall defining at least one wall, which defines via its inner lateral face the volume for retaining the sensitive medium or fluid, on one of the substrates, wherein the outer wall surrounds the inner wall;

- joining the second substrate to the first substrate;

- introducing a sealing material capable of flowing into the ~~gap defined by the outer lateral face of the wall and the two superposed substrates until at least a part of the volume of said gap~~ filling channel until the entire volume of said filling channel is occupied by the sealing material, and

- solidifying the sealing material so that the latter forms the sealing ~~frame~~ joint.

22. (Cancelled)

23. (Currently amended) The method according to claim ~~22~~ 21, wherein a batch of devices is made including two plates common to all of the devices and a network of sealed

walls defining, for each device, a volume for retaining the sensitive medium or fluid as well as the filling channels which are to be filled with a sealing material to connect the two plates and to form the sealing joints of said devices.

24. (Previously presented) The method according to claim 23, wherein a first plurality of holes for filling the volumes with the fluid or sensitive material, and a second plurality of holes for feeding the sealing material, are made in one of the plates.

25. (Previously presented) The method according to claim 23, wherein one filling channel is shared by at least two adjacent devices.

26. (Previously presented) The method according to claim 24, wherein one filling channel is shared by at least two adjacent devices.

27. (Cancelled)

28. (Currently amended) The method according to claim ~~22~~21, wherein the sealing material penetrates the filling channels by capillary action.

29. (Previously presented) The method according to claim 28, wherein it includes the additional steps of:

- creating a vacuum in the filling channel;
- causing the sealing material to enter said filling channel, and
- re-establishing the pressure outside the cell such that, via the pressure difference between the filling channel in which the vacuum prevails and the ambient pressure, the sealing material is driven to the bottom of the filling channel .

30. (Currently amended) The method according to claim 21, wherein a layer of photoresist material, which will subsequently be structured by photo-etching techniques to give it the shape of ~~one or several~~the walls, is deposited on one of the substrates.

31. (Currently amended) The method according to claim 30, wherein the photoresist layer is structured so as to form, not only the ~~wall or~~ walls, but also spacer structures for maintaining a constant distance between the two substrates of the cell.

32. (Currently amended) The method according to claim 21, wherein the ~~wall or~~ walls are structured by a selective technique for depositing the sealing material.

33. (Currently amended) The method according to claim 32, wherein the ~~wall or~~ walls are structured by screen printing.

34. (Currently amended) The method according to claim 32, wherein the ~~wall or~~ walls are structured by means of a ~~seringe~~syringe type dispenser.

35. (Currently amended) The method according to claim 21, wherein the sealing material is selected from the group formed by resins that can be ~~polymerised~~polymerized by ~~sensitisation~~sensitization using a light or by heating by raising the temperature of the ambient medium, by cyanoacrylate adhesives, by thermoplastic resins and by dual component adhesives whose components harden over time or via a rise in temperature when they are placed in each other's presence.

36 -40. (Cancelled)